



JCR Automation, Inc.

1426 Ryan Rd

New Haven, IN 46774

P. 260-493-6606

Wyndmaster 300-2

Automatic Take-up System

Features:

- ◆ Non-stop production capabilities
- ◆ Dual strip
- ◆ **Eight** Reel Capacity
- ◆ Dancer loop and tension control
- ◆ Part/Length counter with operator alert system
- ◆ Programmable operator interface with diagnostics
- ◆ 800 IPM feed rate
- ◆ Quick release reel flanges
- ◆ Casters and floor brakes
- ◆ Quick and simple product changeover
- ◆ Unattended automatic strip transfer

Options:

- ◆ Single spindle paper interleaf
- ◆ Dual spindle paper interleaf with auto splice
- ◆ Sonic non-contact loop control
- ◆ Part count non-contact loop control
- ◆ Wrapped accumulator
- ◆ Non-contact accumulator
- ◆ High speed/high torque motors
- ◆ Part strip locator
- ◆ Collapsible mandrel
- ◆ In-feed puller with encoder
- ◆ Tail retention gripper
- ◆ Over center locking latch fingers
- ◆ Material component selection for corrosive environments



Specifications

Model 300-2 ♦ Automatic Winding System

Power Requirements

110 VAC single phase, 10A

Air Supply

80 PSI @ 5 SCFM

Feed Rate Capabilities

800 IPM with out accumulator

Material Width (max)

3 inches

Reel Diameter (max)

24 inches

Spindle Motor

1/8 HP, 28:1 ratio, 76 RPM, DC

Product Feed

Left to right or right to left (must be specified)

Paint Color

Vista Green (or per customer requirements)

Spindle Configuration

Tooled to customer reel

