

Wyndmaster 324 Four Spindle Automatic Take-up System



FEATURES

- Automatic Cut and Transfer
- Switch Selectable Overwind / Underwind
 Operation
- Non-Contact PC Loop Control
- Four Spindle Operator Start Paper Interleaf
- Tangential Product Feeder
- Adjustable Tension Control
- Part Counter with Operator Alert System
- Programmable Operator Interface with Diagnostics
- Quick Release Reel Flanges
- Sample Strip with Programmable Cut Location
- Single Strip Operation
- Four Reel Capacity

OPTIONS

- Dancer Loop Control
- Programmable Product Tension
- Programmable Paper Tension
- High Speed / High Torque Motors
- Material Component Selection for Corrosive
 Environment
- Automatic Paper Stapler







POWER REQUIREMENTS

120 VAC, single phase, 15A

AIR SUPPLY

80 PSI

MATERIAL WIDTH (MAX)

3 Inches (others available on request)

REEL DIAMETER (MAX)

36 Inches (others available on request)

FEED RATE CAPABILITY

800 IPM Without Accumulator


REEL CENTER CORE


5.0 inches (others available upon request)

FEED DIRECTION Left to right or right to left (Per Customer Request)

SPINDLE MOTORS 76 RPM, 1/8 HP, DC (standard, others available upon request)

SPINDLE DIAMETER 0.75 Inches (Standard, others available on request)







JCR Automation 1426 Ryan Rd New Haven, IN 46774 Phone: 260-493-6606

